CRC® Food Grade White Grease, 10 Wt Oz

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 11/21/2024 Version: 1.0

SECTION 1: Identification

1.1. Identification

Trade name	:	CRC® Food Grade White Grease, 10 Wt Oz
Product code	:	1003292
Part number	:	03038

1.2. Recommended use and restrictions on use

Recommended use	:	Lubricating grease

1.3. Supplier

Manufactured or sold by:
CRC Industries, Inc.
885 Louis Dr.
Warminster, PA 18974
United States
T 1-800-556-5074
crcindustries.com

1.4. Emergency telephone number

Emergency number	:	1-800-424-9300 24-Hour Emergency

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Aerosol, Category 1	Extremely flammable aerosol. Pressurized container: may burst if heated.
Skin corrosion/irritation Category 2	Causes skin irritation.
Specific target organ toxicity – Single exposure, Category 3, Narcosis	May cause drowsiness or dizziness.
Aspiration hazard Category 1	May be fatal if swallowed and enters airways.
Hazardous to the aquatic environment – Acute Hazard Category 2	Toxic to aquatic life.
Hazardous to the aquatic environment – Chronic Hazard Category 3	Harmful to aquatic life with long lasting effects.

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) : Extremely flammable aerosol.
Pressurized container: may burst if heated
May be fatal if swallowed and enters airways
Causes skin irritation
May cause drowsiness or dizziness

Precautionary statements (GHS US) : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.

Do not apply while equipment is energized.
Extinguish all flames, pilot lights, and heaters.
Vapors will accumulate readily and may ignite.
Avoid breathing vapors, spray, mist.
Use only outdoors or in a well-ventilated area.
Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area.
Wear protective gloves.
Wash hands thoroughly after handling.
If swallowed: Immediately call a poison center or doctor.
Do NOT induce vomiting.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
Call a poison center or doctor if you feel unwell.
If on skin: Wash with plenty of water.
If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
Store in a well-ventilated place.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Exposure to high temperature may cause can to burst.
Dispose of contents/container in accordance with local/regional/national regulations.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Ethane, 1,1-difluoro-	1,1-Difluoroethane (HFC-152a)	CAS-No.: 75-37-6	45 – 80
Heptane, branched, cyclic and linear	Heptane, branched, cyclic and linear	CAS-No.: 426260-76-6	10 – 30
Aluminum Complex Grease	Aluminum Complex Grease	CAS-No.: Proprietary	10 – 30

Comments : Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Give oxygen or artificial respiration if necessary. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Wash skin with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing.

First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : None under normal conditions.

Symptoms/effects after ingestion : Risk of lung edema.

4.3. Immediate medical attention and special treatment, if necessary

If swallowed, contact a poison control center or physician immediately.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurized container may rupture when exposed to heat or flame.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

Other information : This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Absorb spillage to prevent material-damage. Notify authorities if product enters sewers or public waters.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapors, spray, mist. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid the spillage or runoff entering drains, sewers or watercourses. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.

Methods for cleaning up : Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Clean surface thoroughly to remove residual contamination.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Exposure to high temperature may cause can to burst. Avoid breathing vapors, spray, mist. Avoid contact with skin and eyes. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear personal protective equipment. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. For product usage instructions, see the product label.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.

Storage conditions : Level 2 Aerosol. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Store in a cool, dry place out of direct sunlight.

Packaging materials : Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Heptane, branched, cyclic and linear (426260-76-6)	
USA - OSHA - Occupational Exposure Limits	
OSHA PEL C	500 ppm

Heptane, branched, cyclic and linear (426260-76-6)	
Occupational Exposure Limit	1500 mg/m³ TLV (ACGIH)

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear protective gloves such as: Butyl rubber

Eye protection:

Safety glasses with side shields

Respiratory protection:

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Color	:	White
Odor	:	Slightly ethereal
Odor threshold	:	No data available
Melting point	:	Not applicable
Freezing point	:	No data available
Boiling point	:	190 °F (87.78 °C) estimated
Flammability (solid, gas)	:	Extremely flammable aerosol.
Explosion limits	:	Lower explosion limit: 1.2 % estimated Upper explosion limit: 6.7 % estimated
Flash point	:	15 °F (-9.44 °C) estimated
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
pH	:	No data available
Viscosity, kinematic	:	< 20.5 mm²/s
Viscosity, dynamic	:	No data available
Solubility	:	No data available
Partition coefficient n-octanol/water (Log Pow)	:	No data available
Vapor pressure	:	No data available
Density and/or relative density		
Density	:	6.55 lb/gal Concentrate
Relative density	:	0.784 Concentrate
Particle characteristics	:	No data available
Relative evaporation rate (butyl acetate=1)	:	No data available
Relative vapor density at 20°C	:	No data available
Explosive properties	:	Pressurized container: may burst if heated.
Oxidizing properties	:	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurized container: may burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO2). Acrid smoke.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Symptoms/effects	:	May cause drowsiness or dizziness.
Symptoms/effects after skin contact	:	Causes skin irritation.
Symptoms/effects after eye contact	:	None under normal conditions.
Symptoms/effects after ingestion	:	Risk of lung edema.
Acute toxicity (oral)	:	Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	:	Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	:	Not classified (Based on available data, the classification criteria are not met)
Skin corrosion/irritation	:	Causes skin irritation.
Serious eye damage/irritation	:	Not classified (Based on available data, the classification criteria are not met)
Respiratory or skin sensitization	:	Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	:	Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	:	Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	:	Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	:	May cause drowsiness or dizziness.
STOT-repeated exposure	:	Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	:	May be fatal if swallowed and enters airways.
Viscosity, kinematic	:	< 20.5 mm²/s

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Ethane, 1,1-difluoro- (75-37-6)	
LC50 - Fish [1]	450 mg/l Source: OECD Screening Information Data Set
EC50 - Crustacea [1]	980 mg/l Source: OECD Screening Information Data Set
EC50 - Other aquatic organisms [1]	146.695 mg/l Test organisms (species): other:
LC50 - Fish [2]	719.611 mg/l Test organisms (species):
EC50 96h - Algae [1]	419 mg/l Source: OECD Screening Information Data Set

12.2. Persistence and degradability

CRC® Food Grade White Grease, 10 Wt Oz	
Persistence and degradability	No data is available on the degradability of this product.

12.3. Bioaccumulative potential

Ethane, 1,1-difluoro- (75-37-6)	
Partition coefficient n-octanol/water (Log Pow)	1.13 Source: SIDS

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation : Disposal must be done according to official regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Sewage disposal recommendations : Disposal must be done according to official regulations. Do not allow to enter sewers, surface or groundwater.

Product/Packaging disposal recommendations : Full or partially-full aerosol cans can be treated as universal waste. Empty container can be recycled. Contents under pressure. Do not pierce or burn, even after use.



Hazardous waste code : Possible RCRA waste code includes:
D001: Ignitable Waste

However, it is the generator's responsibility to determine the proper classification and disposal method at the time of disposal.

Additional information : Do not re-use empty containers.

SECTION 14: Transport information

In accordance with DOT / IMDG / IATA

DOT	IMDG	IATA
14.1. UN number		
1950	1950	1950
14.2. Proper Shipping Name		
Aerosols, flammable (Limited quantity)	AEROSOLS (Limited quantity)	Aerosols, flammable (Limited quantity)
14.3. Transport hazard class(es)		
LTD QTY	LTD QTY	LTD QTY Y
		

DOT	IMDG	IATA
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Marine Pollutant Exception		

14.6. Special precautions for user

DOT

Class (DOT)	:	2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
UN-No.(DOT)	:	1950
DOT Special Provisions (49 CFR 172.102)	:	N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx)	:	306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	:	75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	:	150 kg
DOT Vessel Stowage Location	:	A - The material may be stowed ‘‘on deck’’ or ‘‘under deck’’ on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	:	25 - Shade from radiant heat,87 - Stow ‘‘separated from’’ Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

IMDG

Class (IMDG)	:	2.1 - Flammable gases
Special provision (IMDG)	:	63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	:	SP277
Excepted quantities (IMDG)	:	E0
Packing instructions (IMDG)	:	P207, LP200
Packing provisions (IMDG)	:	PP87, L2
EmS-No. (Fire)	:	F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	:	S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	:	None
Stowage and handling (IMDG)	:	SW1, SW22
Segregation (IMDG)	:	SG69

IATA

Class (IATA)	:	2.1 - Gases : Flammable
PCA Excepted quantities (IATA)	:	E0
PCA Limited quantities (IATA)	:	Y203
PCA limited quantity max net quantity (IATA)	:	30kgG
PCA packing instructions (IATA)	:	203
PCA max net quantity (IATA)	:	75kg
CAO packing instructions (IATA)	:	203
CAO max net quantity (IATA)	:	150kg
Special provision (IATA)	:	A145, A167, A802
ERG code (IATA)	:	10L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Toxic Substances Control Act (TSCA)

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory			
Name	CAS-No.	Commercial status	Flags
Heptane, branched, cyclic and linear	426260-76-6	Active	
Ethane, 1,1-difluoro-	75-37-6	Active	

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not listed

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substance

CERCLA Section 103 (40CFR302.4)	Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986)

Section 302 Extremely Hazardous Substance

Not listed

Section 304 Emergency Release Notification

Not listed

Sections 311/312 Hazard Classification

CRC® Food Grade White Grease, 10 Wt Oz	
SARA Section 311/312 Hazard Classes	Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Skin corrosion or Irritation Health hazard - Specific target organ toxicity (single or repeated exposure) Health hazard - Aspiration hazard

Section 313 (TRI Reporting)

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm. For more information go to www.P65Warnings.ca.gov.

State Regulations

Component	State Regulations
Ethane, 1,1-difluoro-(75-37-6)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List

15.4 Other Regulatory Information

Volatile organic compound (VOC) regulation

EPA

VOC content (40 CFR 51.100(s))	24 %
Consumer products (40 CFR 59, Subpt. C))	Not regulated.

State

Consumer products	This product is regulated as a Multi-Purpose Lubricant.This product is compliant for use in all 50 states.
VOC Content (CA)	24 % (MIR = 0,271)
VOC Content (OTC)	24 %

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Author : Joshua Weir

Safety Data Sheet (SDS), USA, CRC

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries Inc.